

IAP12 Rec'd PCT/PTO 03 MAY 2006

DEVICE AND METHOD FOR CONDITIONING NUCLEAR FUEL
ASSEMBLIES WITH DOUBLE CONFINEMENT BARRIER

TECHNICAL FIELD

This invention relates to conditioning of
5 nuclear fuel assemblies and more particularly to
devices enabling double confinement of assemblies, and
the conditioning procedure in receptacles before
transport or storage, if any.

BACKGROUND ART

10 Nuclear fuel assemblies require particular
procedures for their use, transport and even for
disposal as waste. Thus, irradiated nuclear fuel
assemblies from nuclear power stations have to be
stored after use. Nuclear power plants are provided
15 with a pool in which these assemblies are stored, but
this storage is temporary and the nuclear fuel
assemblies then have to be evacuated to safe so-called
"final" or "interim" storage sites, and in particular
including leak tight metallic confinements protected by
20 concrete storage modules.

To transport them to their destination,
leak tight confinements containing nuclear fuel
assemblies need to be put into place in "temporary"
radiation shielding receptacles. Therefore safety rules
25 that impose confinement of nuclear fuel assemblies in a
leak tight metallic receptacle are respected, the
receptacle itself being placed in a package called the
transfer package with radiation shielding walls. The

metallic receptacle comprises essentially a hollow tubular body with a generally cylindrical shape with a circular cross section, equipped with a closed lower end and a completely open upper end. Document
5 FR 2 805 655 describes an example of this technique.

One conventional possibility for positioning nuclear fuel assemblies in the metallic receptacle and in the transfer package is to use a "dry" or "hot" radiation shielding containment with
10 remote manipulations of the different elements using manipulation arms: it is obvious that working people cannot be close to elements without any radiation shielding. The disadvantage of this method is its complexity, and consequently the time and cost, of the
15 containment and also the tools and manipulation arms.

Since water is good radiation shielding and all power plants have a pool, it has been proposed to package the radiation material directly in pools. In this context, the metallic confinement receptacle is
20 placed in the transfer package, the assembly is immersed in the pool and fuel is loaded into it. The loading opening is then closed off by a radiation shielding closing device that provides protection during the following steps consisting of closure,
25 confinement and transport that take place dry: for example see FR 2 805 655. However, this technique is more restrictive because part of it has to be done while totally immersed in more than ten metres of water. Furthermore, to achieve maximum safety, it is
30 essential to eliminate all residual water in

receptacles before closing them, both in the metallic confinement receptacle and in the transfer package.

However it is possible that an additional confinement, subsequently called the "second
5 confinement" is necessary in addition to the confinement provided by the leak tight metallic receptacle: a second additional containment needs to be put into place. Some legislation imposes this second double containment. In this case, conditioning under
10 water has not been possible up to now, particularly due to problems with drainage of the second confinement containment.

SUMMARY OF THE INVENTION

The invention proposes to solve problems
15 inherent to drainage of double receptacles.

According to one of its aspects, the invention relates to a double receptacles device with a geometry designed to enable drainage and adding of inert gas into the outer receptacle, or checking the
20 seal. Due to the presence of a free passage between the two receptacles, which are also adjusted one in the other, the outer receptacle may be drained for example by a dip tube that descends down to the bottom of the receptacle. Another advantage of this is that all
25 actions can take place on the same upper end of the receptacles, which is preferable for closing after partial exit from the pool, which correspondingly simplifies the tools used, increasing personnel safety.

The two receptacles can be one leak tight
30 metallic receptacle and its radiation shielding

package, but it is also possible that each receptacle is a leak tight metallic conditioning receptacle, the device itself possibly being integrated into a radiation shielding package. A double confinement under
5 water can thus be achieved without making the conditioning system more complicated due to the presence of a dry confinement containment.

Advantageously, the inner receptacle is a leak tight metallic receptacle that includes a central
10 duct, in other words it is annular in section. The inner duct will be used for drainage and for adding inert gas into the outer receptacle and/or for the leak tightness check. Advantageously, a closing plate system is used to make the inner receptacle leak tight before
15 the outer receptacle is closed and drained. The same closing plate system can be used for the outer receptacle.

Another possibility, for example when the shape of the inner receptacle is fixed, is the presence
20 of a protuberance on the outer receptacle that will delimit the passage.

The invention also relates to a double receptacle drainage process, and a process for conditioning radioactive equipment using this drainage
25 process. These processes make it possible to package equipment under water. Advantageously, two leak tight metallic receptacles are used so as to achieve double confinement of the radioactive material without complicating the necessary equipment due to the
30 presence of a dry containment, each step possibly being performed under water.

Another aspect of this invention is a leak tight metallic inner receptacle, the shape of which facilitates existing procedures, particularly concerning draining and therefore sealing the outer receptacle in which it will subsequently be conditioned. Consequently the inner receptacle, composed of a conventional container with a non removable bottom, is also equipped with a duct that passes through the bottom and leaves a free passage when the receptacle is sealed. This passage enables the introduction of gas and/or suction into the receptacle surrounding it.

Other advantages of the invention and some preferred variants will become clearer to those skilled in the art from the following description.

BRIEF DESCRIPTION OF THE FIGURES

The invention will be better understood after studying the appended figures, which are only given for guidance and are in no way limitative.

Figure 1 shows a preferred embodiment of an inner metallic receptacle with baskets and a closing system.

Figure 2 shows an example of a drainage device.

Figure 3 diagrammatically shows possible geometries for the device according to the invention.

Figure 4 diagrammatically shows a drainage procedure according to the invention.

Figure 5 shows a preferred embodiment of the main constituents of a double leak tight metallic receptacles device.

Figure 6 shows an example block diagram of a closing system for a double leak tight metallic receptacles device.

DETAILED DESCRIPTION OF PARTICULAR EMBODIMENTS

Figure 1 shows a metallic confinement receptacle (20), formed from a cylindrical receptacle with sidewalls and a loading opening, closed at its lower end by non-removable bottom. A duct (25) with a circular section also passes through the centreline of the metallic receptacle (20): therefore, the duct has walls along its length but remains open at both its ends. The walls of the receptacle, in other words the sidewalls and the walls of the duct, resist radioactivity but do not necessarily provide radiation shielding. It is obvious that these different forms and arrangements are preferred but not essential examples; for example a receptacle with a parallelepiped shaped section, a side duct and/or a duct with any other shape are other possibilities.

Before loading irradiated fuel assemblies (1), the confinement receptacle (20) is placed in the pool of the nuclear power station. In the context of safety measures and particularly processes according to the invention, the receptacle is usually added firstly into one or two other receptacles, as will be described later.

A basket (2) can be placed inside the metallic receptacle, preferably before immersion in the pool, for the nuclear fuel assemblies (1). Another possibility is the superposition of baskets. For
5 example, within this context it is possible to put the lower basket (3) into place, fill the compartments (5) of the basket with fuel after immersion, and then repeat the operation with the upper basket (4) that has a filter base. Note that in this preferred case, the
10 duct (25) occupies the place of one compartment (5) in the basket.

A filter plate (26) is then preferably placed above the basket(s) to retain impurities in the baskets, without them reaching the closing system.

15 After the metallic receptacle (20) has been loaded, in the pool in the context of the invention, water and all non-inert gases have to be evacuated from the confinement.

One of the options selected to facilitate
20 drainage of the metallic receptacle is to provide means of draining the receptacle; one preferred example of the drainage means is shown in Figure 2. In fact, a drainage device (22) equipped with two self-closing orifices and a dip tube (23) is placed in the upper
25 part of the receptacle, along the wall that does not form part of the duct; preferably, it is located above a space left free by the compartments (5) and welded to the wall. The dip tube (23) is preferably connected by welding to one of the two self-closing orifices of the
30 device (22); the second orifice (24) opens up under the device and acts as a vent. The drainage device (22) can

also be welded with its dip tube (23) before the baskets (2, 3, 4) are put into place.

A shielded plug (27) is placed above the filter plate, to provide axial radiation shielding during drainage and closing operations. However, this shielded plug leaves access to the drainage device (22) equipped with the free dip tube (23): this enables drainage and the addition of inert gas into the receptacle. Due to the plug (27), it is then possible to take the metallic receptacle (20) and the receptacle(s) surrounding it from the pool that provides radial radiation shielding.

One preferred possible method of keeping the shielded plug (27) in position is to use a primary closing plate (28). The water level is lowered in receptacle just below the level of the shielded plug (27). The primary closing plate (28) is then put into place, for example by welding, along the walls of the duct (25), of the metallic receptacle (20) and of the drainage device (22). The metallic receptacle can then be drained.

One of the methods used for drainage consists of injecting compressed air through the self-closing orifice (24), or by suction through the drainage tube (23). The metallic receptacle (20) is then drained and dried by vacuum suction; drying can be checked by a pressure rise test. Finally, an inert gas is injected (N_2 or preferably He). Preferably, the top end of the drainage device (22) is then closed by welding an orifice plate (28') (see Figure 5).

A secondary annular-shaped closing plate (29) is housed inside the walls of the metallic receptacle (20) above the primary plate (28), but it also covers the drainage device (22) so as to make the metallic receptacle leak tight, for example by welding. The presence of this plate (29) also makes it possible to check the leak tightness of the assembly formed beforehand, by checking gas exchange.

Note that the fuel is then confined in the metallic receptacle (20) that forms a closed volume, except for the duct (25) that passes through the primary closing plate (28) and the secondary closing plate (29), and the bottom of the receptacle (20). The duct (25) is used for drainage of the receptacle surrounding the first metallic confinement receptacle: the duct leaves a free passage that will enable gas and liquid exchanges to take place in both ways in the receptacle (30, 40) surrounding the metallic receptacle (20).

As already mentioned, the leak tight metallic confinement receptacle (20) is usually located in a second receptacle (30). The two receptacles are adjusted: the space separating them is preferably minimum; it is also desirable to prevent movement between the two receptacles and to limit the residual gas volume between the two receptacles that is prejudicial to heat exchanges. For example, when two leak tight cylindrical metallic receptacles (20, 30) are considered, a clearance of a few millimetres (1 cm maximum) between the two receptacles with a diameter of the order of 1 m - 1.5 m is usually tolerated (the

normal length is 3 to 4.5 m with an approximately 80 mm diameter duct, namely the size of a fuel assembly).

However, within the framework of the invention and so that all operations can be performed
5 under water, the second receptacle, or outer receptacle, was present in the pool for example under 10 m of water. Therefore, water remains between the two receptacles regardless of the adjustment between the two volumes, and the outer receptacle has to be
10 drained.

Although the duct is a preferred solution to enable drainage for a cylindrical receptacle, in fact all that is necessary is for a single passage (15) to remain free between the two receptacles (20, 30) when one is located in the other. For example, if the
15 inner metallic conditioning receptacle does not have a duct, it is possible to adapt the geometries of the two receptacles (20, 30) so as to have a sufficiently large passage while tolerating the 1% adjustment tolerance
20 over most of the surface. Thus, Figures 3a, 3b and 3c show different possible geometry types to achieve this result; these options also form part of the invention. Figure 3a shows the embodiment with a duct according to the invention that is preferred because the symmetric
25 receptacles are easier to manipulate during automated welding procedures. Figure 3c may be recommended for example if the shape of the fuel baskets cannot be adapted to the "hole" necessary for the duct to pass through. In this case, a protuberance (35) on the outer
30 receptacle (30) performs the same function.

The drainage process is then as follows:
the device (10) is prepared, with placement of the
inner metallic receptacle (20) in the outer receptacle
(30) and immersion into the loading pool (Figure 4a).
5 To facilitate and optimise future drainage procedures,
it is preferable to leave a clearance at the bottom
between the two receptacles, for example through spacer
pads (37). The inner metallic receptacle is filled and
made leak tight, for example using the procedure
10 described above (Figure 4b).

The outer receptacle is closed by means of
a leak tight head (38) including a drainage device (32)
welded in the central part as shown in the figure,
similar to the device used to drain the inner
15 receptacle or as shown in Figure 2: the drainage device
(32) is thus equipped with a first self-closing orifice
to which a dip tube (33) is connected, and a second
self-closing orifice (34) opening under the drainage
device and acting as a vent (see Figure 5). The
20 drainage device (32) is actually located facing the
passage (15) such that the dip tube (33) can penetrate
into the passage. It can then be drained (Figure 4c):
compressed air is injected through the orifice (34) or
suction takes place through the drainage tube (33) to
25 remove residual water. Drainage and drying then take
place through vacuum suction. Preferably, a check of
the leak tightness of the outer receptacle can be made
through the passage (15), for example by a pressure
rise test. Similarly, a drying check can be made by a
30 pressure rise test. Finally, an inert gas (He or N₂) is
injected.

The next step is to close off the two self-closing orifices, for example by welding an orifice plate (38') above the drainage device (32) so as to achieve confinement. In the same way as for the inner
5 metallic receptacle, the seal can be made using a second leak tight head (39) that will be welded to the outer casing (30) (Figure 4d) and this leak tightness can be checked, particularly by a pressure rise in the space between the covers (38, 39).

10 The outer receptacle (30) may be a storage and/or transfer package (40), for which the sidewalls are then radiation shielding. This package is closed at its lower end (in the direction of Figure 4), removably or non-removably depending on the unloading procedure
15 used in the storage site. It is provided with a cover (38) at its other end. For example this cover may be screwed, but if long-term storage is planned, it can be welded. Usually, if screwing is used, the self-closing orifices are closed by closing off with a head and then
20 with a plug, before final sealing.

The device drainage and method according to the invention makes the closing method simpler than existing procedures. In this case, unlike the device described in document US 4 780 269, only the head (38)
25 is provided with a drainage device (32) used for drainage and to add inert gases and/or for checking the leak tightness; all actions following drainage and closure are carried out at this same end of the package. Therefore, there is no need to have a second
30 system to close a lateral orifice at the bottom of the package. Furthermore, methods using transfer packages

with a single orifice used in the state of the art require complex procedures to prevent water from entering between the two receptacles and check means to assure that the leak tightness has been maintained.

5 Therefore, another advantage of the drainage method according to the invention is the possibility of creating a double confinement. This is done by choosing the outer receptacle as being a second metallic confinement receptacle (30). A second metallic
10 receptacle has a non-removable bottom and will normally be made "permanently" leak tight. Figure 5 shows that the bottom of the outer metallic receptacle can provide radiation shielding, but this is not necessary. It may include spacer pads (37).

15 The closing/drainage procedure of the outer metallic receptacle (30) is similar to that described above for the inner metallic receptacle (20). The radiation shielding plug is not useful in this case, since radiation shielding is provided by the plug (27)
20 of the inner metallic receptacle (20). A second primary closing plate (38) is provided to close the second metallic receptacle (30): it is provided with a drainage device (32) at its centre provided with a dip tube (33) that penetrates into the duct (25) that
25 remained free, for drainage and for addition of inert gas into the second outer metallic receptacle (30). Similarly, the primary closing plate (38) may be fixed by welding. Finally after drainage and addition of inert gas, a second secondary closing plate (39) that
30 is circular in this example, will make the second

metallic receptacle (30) leak tight, possibly with a leak tightness check.

Although the assembly (10) of the two metallic receptacles (20, 30) is used for storage or transport, it is also possible to condition the outer metallic receptacle (30) in a transfer package (40) with radiation shielding walls using known methods.

Leak tightness of each metallic receptacle (20, 30) can be made by any appropriate techniques, such as manual welding.

An automatic welding method is proposed to further increase safety (see Figures 6a to 6f), particularly suitable within the framework of the double confinement presented.

a. Figure 6a shows preparation of the conditioning assembly with the inner metallic receptacle (20) inserted into the outer metallic receptacle (30), itself integrated into the transfer package (40) through a seal, in this case an inflatable seal. The nuclear fuel assemblies (1) are placed in the basket.

b. Once the metallic receptacle (20) has been filled, a shielded plug (27) is placed above a filter plate (26), and the full transfer package (40) is partially removed from the pool and placed in the "preparation, welding" area. The water level in the transfer package (40) is lowered by suction using special purpose tools, to just below the shielded plug (27).

c. The primary closing plate (28) of the inner metallic receptacle (20) is then put into place.

The plate is welded on the outside onto the shell and onto the drainage device (22) and inner welding is done (on the central duct (25)); this welding is done using a previously positioned automatic welding machine.

5 d. As described above, inert gases are injected into the inner metallic receptacle (20) through one of the two self-closing orifices of the drainage device (22), and the secondary closing plate (29) of the inner metallic receptacle is welded on the
10 outside (on the shell) and on the inside (on the central duct) using the previously positioned automatic welding machine.

 e. The primary closing plate (38) of the outer metallic receptacle (30) is also welded, and its
15 drainage device (32) is positioned facing the duct (25) using the previously positioned automatic welding machine, with drainage and addition of inert gas into the outer metallic receptacle (30).

 f. Finally, the secondary closing plate
20 (39) of the outer metallic receptacle is put into position before the closing weld of the closing plate is made using the previously positioned automatic welding machine.

25

LIST OF REFERENCE SIGNS

	1	radioactive fuel assembly
	2	basket for assembly
5	3,4	superposable baskets
	5	compartment
	10	conditioning device
	15	device passage
	20	inner leak tight receptacle
10	22	drainage device with orifices
	23	inner receptacle dip tube
	24	self-closing orifice of the drainage device
	25	duct
	26	upper filter plate
15	27	shielded plug
	28	inner receptacle primary closing plate
	28'	inner receptacle drainage device closing plate
	29	inner receptacle secondary closing plate
20	30	outer receptacle
	32	drainage device for the outer receptacle
	33	outer receptacle dip tube
	34	self-closing orifice of the drainage device
	35	protuberance of the outer receptacle
25	37	spacer pad
	38	outer receptacle primary closing plate
	38'	outer receptacle drainage device closing plate
	39	outer receptacle secondary closing plate
30	40	transfer package